





Unilift 870 Kitchen appliance lift

UNILIFT lifts a panel upwards and outwards from the bottom of a floor or wall cupboard. It can be used to lift food processors, microwaves or other household appliances.

A simple push of a button adjusts the height of the panel to the optimum working height.





Quick facts

- \checkmark Lifts up heavy household appliances to a convenient height
- ✓ Can be stopped at optional height
- \checkmark Simple to install in the bottom of a floor or wall cupboard
- ✓ Can be fitted in new or existing cupboards

Unilift 870

ORDERING INFORMATION

Unilifi The lift's width: 34.0 cm 870-034 Image: Source of Solid variables of Solid varia	ic option			Basic option	
870-034 For one lift Hand control Hand control Corded hand control. Mounting fittings included. Dimensions: 14.7 x 5.6 x 2.3 cm Worktop The top is made of solid varnished beech. Depth: 35.0 cm B91-033 Thickness: 2.8 cm 891-033 Width: 43.0 cm 891-043 Width: 43.0 cm 891-043 Width: 43.0 cm 891-053		Unilift		3.	Radio control - Hand control
Worktop Worktop The top is made of solid varnished beech. Depth: 35.0 cm B91-033 Thickness: 2.8 cm With: 33.0 cm With: 33.0 cm 891-043 (For cupboard width 50.0 cm) 891-043 Width: 43.0 cm 891-053		The lift's width: 34.0 cm		6	
Corded hand control. Mounting fittings included. Dimensions: 14.7 x 5.6 x 2.3 cm Worktop The top is made of solid varished beech. Depth: 35.0 cm Thickness: 2.8 cm Width: 33.0 cm (For cupboard width 40.0 cm) Width: 43.0 cm (For cupboard width 50.0 cm) Width: 43.0 cm (For cupboard width 50.0 cm) Width: 43.0 cm	Á		870-034	CF .	For one lift
Worktop Interview Intervi					Hand control
The top is made of solid varnished beech. Depth: 35.0 cm Thickness: 2.8 cm Width: 33.0 cm (For cupboard width 40.0 cm) Width: 43.0 cm (For cupboard width 50.0 cm) Width: 43.0 cm 891-043	1				fittings included.
The top is made of solid varnished beech. Depth: 35.0 cm Thickness: 2.8 cm Width: 33.0 cm (For cupboard width 40.0 cm) Width: 43.0 cm (For cupboard width 50.0 cm) Width: 43.0 cm 891-043					
varnished beech. Depth: 35.0 cm Thickness: 2.8 cm 891-033 Width: 33.0 cm 891-043 (For cupboard width 40.0 cm) 891-043 Width: 43.0 cm 891-053		Worktop			
(For cupboard width 40.0 cm) Width: 43.0 cm (For cupboard width 50.0 cm) Width: 43.0 cm 891-053	5577/2	varnished beech. Depth: 35.0 cm			
(For cupboard width 50.0 cm) 891-053	and the second s		891-033		
			891-043		
			891-053		

TECHNICAL INFORMATION

Type of lift: Universal lift that lifts up a panel from the bottom of a floor or wall cupboard Adjustability: Motor-driven, continuously adjustable 74.5 cm upwards, 50.0 cm out from the cupboard Speed: 3.7 cm / sec. Operation: Corded hand control or remote control

50.0

Electrical connection: Mains plug for 230 V, max 1,5A Max. load on panel: 20 kg

Frame height: 66.0 cm Frame width: 34.0 cm Fits cabinet width: 40.0 - 60.0 cm

CE

Material: Powder coated sheet-metal parts (Alu-grey RAL 9006)

55.5





67.0

11111111111

Unilift 870

3



Granberg Interior AB Box 6112 • 600 06 Norrköping • Sweden Tel: +46 (0)11-19 77 50 • Fax: +46 (0)11-12 76 76 E-mail: info@granberg.se • Internet: www.granberg.se