

# LOOX 24V LED 3010 DOWNLIGHT


Recessed or with two options for surface mounting, this 3.25W light provides excellent output



## Loox 24V LED 3010 downlight, Ø 65 mm



Choice of clear or frosted glass cover included



IP20



> Note: This light is not dimmable

Distance	105°	3000 K	4000 K	6000 K
250 mm		1085 Lx	1157 Lx	1300 Lx
500 mm		325 Lx	355 Lx	421 Lx
750 mm		154 Lx	184 Lx	211 Lx
1000 mm		71 Lx	81 Lx	84 Lx



> For surface mounting order bezel Cat. No. 833.77.730 or rectangular housing Cat. No. 833.77.731 separately, shown on page **75**



> Order Loox 24V driver and mains lead separately, shown on page **98**  
> Order switch separately, switches shown on pages **134-136**


- > For recess mounting, press-fit in Ø 60 mm hole
- > Voltage: 24V. Wattage: 3.25W
- > With 2.0 m lead with Loox 24V connector
- > Silver coloured anodised aluminium with clear glass cover, optional replacement frosted glass cover also included
- > Order qty: 1 pc

Output:	3000 K	4000 K	6000 K
Light colour:	Warm white	Cool white	Daylight white
Number of diodes:	1	1	1
Light output (Lm):	180	204	204
Wattage (W):	3.25	3.25	3.25
Efficacy (Lm/W):	55	63	63
Colour Rendering Index:	82	84	83



Finish	3000 K	4000 K	6000 K
Silver coloured	833.75.040	833.75.041	833.75.042

## Loox 24V LED 3010 bezel, Ø 66.5 mm






- > For surface mounting Loox LED 3010 downlight
- > Screw fixing, fixings included
- > Aluminium
- > Order qty: 1 pc



Finish  
Silver anodised

Cat. No.  
833.77.730

## Loox 24V LED 3010 housing, 200 x 75 mm



- > For surface mounting Loox LED 3010 downlight
- > Screw fixing, fixings included
- > Aluminium
- > Order qty: 1 pc



Finish  
Silver anodised

Cat. No.  
833.77.731