


# LOOX 24V LED 3001 DOWNLIGHT

Recess mounting downlight, with optional bezel for surface mounting.



## Loox 24V LED 3001 downlight, Ø 65 mm



IP20

- > For recess mounting, press-fit in Ø 55 mm hole
- > Voltage: 24V. Wattage: 1.7W
- > With 2.5 m lead with Loox 24V connector
- > Silver coloured anodised aluminium, with prismatic cover
- > Order qty: 1 pc or set

Distance	55°	3200 K	5000 K
250 mm		1900 Lx	2000 Lx
500 mm		490 Lx	500 Lx
750 mm		220 Lx	230 Lx
1000 mm		150 Lx	160 Lx

Output:	3200 K	5000 K
Light colour:	Warm white	Cool white
Number of diodes:	24	24
Light output (Lm):	90	100
Wattage (W):	1.7	1.7
Efficacy (Lm/W):	53	59
Colour Rendering Index:	82	90




	3200 K	5000 K
<b>Single light only</b>	833.75.010	833.75.000
<b>Set with lights, driver, mains lead and bezels</b>		
2 light set	-	833.75.004
3 light set	-	833.75.005



- > For surface mounting order bezel Cat. No. 833.77.710 separately, shown below

## Loox 24V LED 3001 bezel, Ø 68 mm



- > For surface mounting Loox LED 3001 downlight
- > Screw fixing, fixings included
- > Aluminium
- > Order qty: 1 pc



Finish	Cat. No.
Silver coloured	833.77.710



- > Order Loox 24V driver and mains lead separately, shown on page 98
- > Order switch separately, switches shown on pages 134-136

PAGE AMENDED  
04.02.15/1