


# LOOX 12V LED 2020 DOWNLIGHT

Loox

This light is suitable for use in wet areas (zone 1) of bathrooms or kitchens when recess mounted. It also has an opaque cover which provides an even distribution of light.



## Loox 12V LED 2020 downlight, Ø 65 mm, IP44 rated



IP44

- > For recess mounting, press-fit in Ø 55 mm hole
- > Voltage: 12V. Wattage: 3.2W
- > With 2.0 m lead with Loxx 12V connector
- > Zinc alloy housing with opaque lamp cover
- > Order qty: 1 pc

Output:	3000 K	4000 K	6000 K
Light colour:	Warm white	Cool white	Daylight white
Number of diodes:	6	6	6
Light output (Lm):	122	138	138
Wattage (W):	3.2	3.2	3.2
Efficacy (Lm/W):	38	43	43
Colour Rendering Index:	85	85	85




Finish	3000 K	4000 K	6000 K
Matt nickel	833.72.020	833.72.021	833.72.022
Polished chrome	833.72.030	833.72.031	833.72.032

Distance	110°	3000 K	4000 K	6000 K
250 mm		766 Lx	848 Lx	848 Lx
500 mm		191 Lx	212 Lx	212 Lx
750 mm		85 Lx	94 Lx	94 Lx
1000 mm		48 Lx	53 Lx	53 Lx



- > Order bezel separately for surface mounting

## Loox 12V LED 2020 bezel, Ø 66.5 mm



- > Note: IP rating is 20 when light is surface mounted



- > For surface mounting Loxx LED 2020 downlight
- > Screw fixing, fixings included
- > Zinc alloy
- > Order qty: 1 pc



Finish	Cat. No.
Nickel silver coloured	833.72.800
Polished chrome	833.72.802



- > Order Loxx 12V driver and mains lead separately, shown on page 62
- > Order switch separately, switches shown on pages 134-136

PAGE AMENDED  
20.03.15/1